Interdisciplinary Studies on Environmental Chemistry—Marine Environmental Modeling & Analysis, Eds., K. Omori, X. Guo, N. Yoshie, N. Fujii, I. C. Handoh, A. Isobe and S. Tanabe, pp. 117–123. © by TERRAPUB, 2011.

Spatial Variation of Submarine Groundwater Discharge (SGD) in the Central Part of Seto Inland Sea, Japan

Mitsuyo SAITO¹, Xinyu GUO¹, Shin-ichi ONODERA², Yuta SHIMIZU², Yoshiaki KATO², Minoru TOKUMASU³ and Hidetaka TAKEOKA¹

 ¹Center for Marine Environmental Studies (CMES), Ehime University, Bunkyo-cho 2-5, Matsuyama 790-8577, Japan
²Graduate School of Integrated Arts and Sciences, Hiroshima University, Kagamiyama 1-7-1, Higashi-Hiroshima 739-8521, Japan
³Saijyo City Office, Akeyashiki 164, Saijyo 793-8601, Japan

(Received 1 November 2010; accepted 12 January 2011)

Abstract—We measured the spatial distribution of salinity and radon-222 (222 Rn) concentration within seawater in the Hiuchi-Nada, a small bay located in central part of the Seto Inland Sea, to clarify the groundwater discharge distribution in weak stratification period of 2009. The results suggest that the shallow (unconfined) groundwater discharged near the coastline, while deep (confined) groundwater discharged from offshore seabed in southwestern area of the study area. The average contribution of groundwater to seawater in the study area is estimated to be about 2%.

Keywords: submarine groundwater discharge (SGD), spatial variation, Seto Inland Sea, Radon-222 (222 Rn)

INTRODUCTION

Submarine groundwater discharge (SGD) represents all direct discharge of subsurface fluids across the land-ocean interface (Taniguchi *et al.*, 2002). Recent studies have revealed that SGD is one of the important pathways for nutrients and the other dissolved materials such as carbon and trace metals from terrestrial area to the marine environment (Moore, 2010). On the global scale, Zektser and Loaiciga (1993) estimated that the amount of dissolved material load by direct groundwater discharge is more than 50% of that from rivers. Accordingly, the effect of groundwater cannot be negligible in considering nutrient environment of coastal area.

Based on the conceptual figure shown by Taniguchi *et al.* (2002), submarine fresh groundwater discharge (SFGD) includes shallow (unconfined) groundwater and deep (confined) groundwater. In additj"b, shallow groundwater generally discharges near the coast line, while deep groundwater would discharges from the seabed of offshore area because it has higher water pressure than shallow groundwater. However, in the previous studies, discharge area and its flux of the



Fig. 1. Study area (a: location of the study area and b: sampling stations).

deep groundwater in the coastal areas were not well evaluated.

Seto Inland Sea is the largest semi-enclosed coastal sea in Japan. Recently, some researchers tried to evaluate SGD at the specific area of the Seto Inland Sea. For example, Taniguchi and Iwakawa (2004) evaluated shallow groundwater discharge in the Osaka Bay using seepage meters. Onodera *et al.* (2007) examined shallow groundwater discharge and derived nutrient transport in a small tidal flat located on an island. Shimizu *et al.* (2009) estimated the shallow groundwater discharge along the coast line of Bisan-Seto using topographic model. Nevertheless, deep groundwater discharge was not evaluated in these studies.

The objective of the study is to confirm the presence of SGD including both of shallow and deep groundwater and its spatial distribution in the central area of Seto Inland Sea.

STUDY AREA

The Hiuchi-Nada is a semi-enclosed bay in the central part of the Seto Inland



Fig. 2. Vertical profiles of (a) salinity, (b) temperature and (c) sigma-t measured at all stations.

Sea. The bay has a size of about 50 km \times 30 km and an average depth of approximately 20 m. Kurushima Strait, a narrow and deep strait (>50 m), is located at its western side, and Bisan Strait, a wide and shallow strait, at its eastern side.

The study area (Fig. 1) is southwestern part of the Hiuchi-Nada and has a size of approximately $30 \text{ km} \times 13 \text{ km}$. Based on the horizontal distribution of residual current in the Hiuchi-Nada (Guo *et al.*, 2004), we know that dominant dub-tidal current flows from east to west along coastal line. Only some small rivers (Kamo River, Nakayama River etc.) flow into the study area, whereas the terrestrial area is characterized by abundant volume of groundwater recharged in the catchment of mount Ishizuchi, which is the highest mountain (max. 1982 m amsl.) in western Japan.

METHOD

We conducted the measurement of vertical profiles in salinity, water temperature and chlorophyll and sampling of sea water at intervals of 5 m from the surface to the bottom at 15 stations with depth of from 10 m to 25 m in September 2009 (Fig. 1). River water samples and terrestrial groundwater samples were collected around the study area. Radon-222 (²²²Rn) concentration was measured at surface and bottom layers of the sampling station using electronic radon detector (RAD7, Durridge Co.). ²²²Rn is one of the radioactive isotopes of radon in the uranium-238 (²³⁸U) series. It is unreactive in nature with short half-life (t_{1/2} = 3.83 d). Burnett *et al.* (1996) pointed out that the Radon-222 (²²²Rn) is a useful tracer of SGD because groundwater has extremely high



Fig. 3. Salinity distribution in surface (a) and bottom (b) seawater.

concentration in ²²²Rn compared with river water and seawater. Therefore, relatively high ²²²Rn concentration in seawater suggests groundwater discharge area.

RESULTS AND DISCUSSION

Spatial distribution of groundwater discharge area

Figure 2 summarized vertical profiles of (a) salinity, (b) water temperature and (c) sigma-t at all sampling stations. Salinity and sigma-t were relatively low while temperature was high in the upper layer. These results indicate the presence of stratification with a pycnocline at depth of about 5 m.

Salinity in the surface layer was relatively low near the coastline, indicating the influence of river water inflow. Figure 3 shows horizontal distribution of salinity in (a) surface and (b) bottom seawater. In the surface layer, low salinity less than 26 was detected at some stations near the coastline; in the bottom layer, salinity was about 32–33 with a smaller spatial variation than in surface layer.

Figure 4 is the horizontal distribution of ²²²Rn concentration in (a) surface and (b) bottom seawater. Here, ²²²Rn concentration is expressed as the ratio of the



Fig. 4. ²²²Rn distribution in surface (a) and bottom (b) seawater.

concentration in each station to the lowest concentration (HN-11). ²²²Rn concentration in the surface layer was relatively high along the coast line. This result suggests the effect of river inflow and shallow (unconfined) groundwater discharge near the coast line. Meanwhile, in the bottom layer, high ²²²Rn concentration was detected in the offshore area at southern part of the study area. As mentioned above, the observation was conducted in stratification period (Fig. 2). Therefore, the result indicates that deep (confined) groundwater discharge more offshore area than the shallow groundwater.

The spatial variation of salinity and ²²²Rn concentration presented almost the same trend, which was more significant in ²²²Rn than in salinity. This can be easily understood from the fact that salinity is almost same between river water and groundwater, whereas ²²²Rn concentration is generally higher in groundwater than in river water (Burnett *et al.*, 1996). For this reason, ²²²Rn is a good tracer for separating the effect of river water and groundwater within seawater, as shown by our measurement results. It must be noted that our measurements confirmed presence of deep groundwater discharge in the coastal area (Fig. 4b), which correspond well to the concept of SGD given by Taniguchi *et al.* (2002).



Fig. 5. Relation between salinity and ²²²Rn in the seawater, groundwater and river water.

Estimation of groundwater contribution in the seawater

Figure 5 shows the relation between salinity shown as electric conductivity (EC) and ²²²Rn concentration in the surface and bottom seawater. Surface seawater is characterized by lower salinity than bottom seawater. Here, we hypothesized that the seawater in the study area is composed of simple binary mixing between offshore seawater and terrestrial water (river water or groundwater). The offshore seawater is assumed to be the bottom seawater at station HN-11 located in the northeastern area (Fig. 1c). According to the distribution of residual currents in the Hiuchi-Nada given by Guo *et al.* (2004), offshore seawater would flow in the study area from eastern part, and flow out from western part (Fig. 1c). Since the bottom seawater at station HN-11 is characterized by the lowest ²²²Rn concentration and relatively high salinity among all stations, it should be little influenced by fresh terrestrial water inflow.

The gray color zone in Fig. 5 shows the mixing between offshore seawater and river water or that between offshore seawater and groundwater. Here, the mixing is not given as a single "line", because the ²²²Rn concentration in terrestrial water has spatial variations among sampling sites (Fig. 1c). The result suggests that the bottom seawater in the study area would be originated by the mixing between offshore seawater and the groundwater, while the surface seawater would be influenced by river water. The average contribution of groundwater is estimated to be about 2% among all sampling stations.

CONCLUDING REMARKS

To confirm the groundwater discharge area in the Hiuchi-Nada, we have measured the spatial distribution of salinity and radon-222 (²²²Rn) concentration in the surface and bottom seawater during the stratification period of 2009. Significantly low salinity in the surface seawater indicates the effect of river inflow. Spatial distribution in ²²²Rn concentration suggests that shallow (unconfined) groundwater discharges near the coastline, while deep (confined) groundwater discharges from the offshore seabed in southwestern area of the study area. The average contribution of groundwater to the seawater in the study area is estimated to be about 2%.

Acknowledgments—This research was supported by the research grant of Research Institute for the Seto Inland Sea. The authors are grateful to Mr. Onishi and students from Center for Marine Environmental Studies, Ehime University and Mr. Ikawa from Saijyo City Office for their help to our field work. Xinyu Guo acknowledges the support from the Global COE (Centers of Excellence) Program and the Grants-in-Aid for Scientific Research (21310012) from JSPS.

REFERENCES

- Burnett, W. C., J. E. Cable, D. R. Corbett and J. P. Chanton (1996): Tracing groundwater flow into surface waters using natural ²²²Rn. p. 22–28. In *Groundwater Discharge in the Coastal Zone*, ed. by R. W. Buddemeier, LOICZ, Texel, The Netherlands.
- Guo, X., A. Futamura and H. Takeoka (2004): Residual currents in a semi-enclosed bay of the Seto Inland Sea, Japan. J. Geophys. Res., **109**, C12008, doi:10.1029/2003JC002203.
- Moore, W. S. (2010): The effect of submarine groundwater discharge on the ocean. *Annu. Rev. Mar. Sci.*, **2**, 59–88.
- Onodera, S., M. Saito, M. Hayashi and M. Sawano (2007): Nutrient dynamics with groundwaterseawater interactions in a beach slope of a steep island, western Japan. *IAHS Publ.*, **312**, 150– 158.
- Shimizu, Y., S. Onodera and M. Saito (2009): Estimation of spatial variation in submarine groundwater discharges from a coastal grid 50 m square, using a topographic model: an example of the application to the middle of the Seto Inland Sea. *Japanese J. Limnol.*, **70**, 129–139 (in Japanese).
- Taniguchi, M. and H. Iwakawa (2004): Submarine groundwater discharge in Osaka bay, Japan. *Limnology*, **5**, 25–32.
- Taniguchi, M., W. C. Burnett, J. E. Cable and J. V. Turner (2002): Investigation of submarine groundwater discharge. *Hydrol. Proc.*, 16, 2115–2129.
- Zektser, I. S. and H. G. Loaiciga (1993): Groundwater fluxes in the global hydrologic cycle: past, present and future. J. Hydrol., 144, 405–427.

M. Saito (e-mail: misaito@sci.ehime-u.ac.jp)